


P.C.B. LAYOUT
SCALE 2.00



Note:

1. Material:

- 1.1 Insulator: PBT UL 94-V0 rated
- 1.2 Contact: phosphor bronze, t=0.25mm
- 1.3 Shell: brass, t=0.4mm

2. specification:

- 2.1 Current rating: 1A MAX
- 2.2 Dielectric withstanding voltage: 500 v(ac) far minuta
- 2.3 Contact resistance: 30 mΩ max
- 2.4 Insulation resistance: 1000 mΩ min at DC 500V.
- 2.5 Temperature range: -55°C~+105°C

3. Finishes:

- 3.1 Contacts: Gold flashed 1U", 3U", 5U", 10U", 15U", 30U"
- 3.2 Shell: Nickel plated.

3	MINI USB 5P銅殼	1	Brass	T=0,4±0.02mm	Nickel Plated	D3520XX
2	MINI USB 5PIN 90° 母頭 (鍍X 2 PIN)	5	PHOSPHOS BRONZE	T=0.25±0.02mm	Gold Plated Over Tin	A0760XX
	MINI USB 5PIN 90° 母頭 (鍍X 3 PIN)					A0760XX-A
1	膠心	1	P.B.T+30%GF		Black/Blue/White	
No.	Part Name	Q'ty	Material	Thickness	Finish	Notes

Oznaczenie	MUSB-05 BR	
Opis	MINI USB 5P FEMALE B TYPE RIGHT ANGLE LOW-LEAD	
	WW elektronik s.c. ul. Kraszewskiego 26 81-815 Sopot	Tel. 058 551-11-15 fax. 058 550-45-17 e-mail: info@wwelektronik.com.pl
	www.wwelektronik.com.pl	