

Features:

- * Available in 2 thru 24 circuit housing
- * Voltage rating 600V (R.M.S.)
- * Current rating 9 Amps per circuit





Specification:

Material:

- * UL 94V-2 nylon 66


Electrical:

- * Voltage rating: 600V AC/DC
- * Current rating: 9A max
- * Withstanding Voltage: 1500V AC for 60 seconds
- * Insulation Resistance: 1000M ohms min
- * Temperature Rise: 30°C max
- * Storage Temperature Range: -40°C to 105°C



Mounting Hole Details for 4259-NE Housing

Max. Panel Thickness: 2.54mm



Dimensional Information (mm)

Circuits	Dim. A	Dim. B	Dim. C	Dim. D	Circuits	Dim. A	Dim. B	Dim. C	Dim. D	Circuits	Dim. A	Dim. B	Dim. C	Dim. D
2		5.4	5.8	10.8	10	16.8	22.2	22.0	27.6	18	33.0	39.0	30.4	44.4
4	4.2	9.8	10.0	15.0	12	21.0	26.4	26.8	31.8	20	37.8	43.2	43.6	48.0
6	8.4	13.8	14.2	19.2	14	25.2	30.6	31.0	36.0	22	42.0	47.4	47.8	52.8
8	12.6	18.0	18.4	23.4	16	29.4	34.8	35.2	40.2	24	46.2	51.6	52.0	57.0

Oznaczenie	JS-1148		
Opis	Mini-Fit dual row male 4,20mm		
	WW elektronik s.c. ul. Kraszewskiego 26 81-815 Sopot		Tel. 058 551-11-15 fax. 058 550-45-17 e-mail: info@wwelektronik.com.pl
	www.wwelektronik.com.pl		