


CCF02001 - Plug

Number of poles: 2, Spring tightening, 12A, 2.5mm², 12AWG, 300V, Pitch 5 mm, Side stackable, Wiring mode Straight, Green (RAL 6032), Soldering technology Not applicable, UL, IEC



Number of poles:	2
Number of levels:	1
Sides configuration:	Side stackable
Pitch:	5 mm
Voltage:	300 V
Current :	12 A
Wire section:	0.05 ÷ 2.5 mm ²
Available approvals:	UL, IEC

General Data

Features

Screw dimension	na
Stripping length	10 mm
Operating temperature range	-40°C ÷ 105°C
Contact resistance	<15 mOhm
Insulation resistance	>1 GOhm

Certifications

IEC (n.EN61984)

Rated voltage	300 V		
Nominal current	12 A		
Wire section	2.5 mm ²		
Insulating category	I		
Overvoltage category/Pollution degree	III/3	II/2	II/2
Impulse voltage	4kV	4kV	4kV
Rated voltage	300V	300V	600V
Insulation voltage	320V	320V	630V

UL (n.E167473)

Rated voltage	300 V
Nominal current	12 A
Wire section	12 AWG

Materials


Components

Spring contact	Tin-plated copper alloy
Spring tightening	Stainless steel
Insulating housing material	PA Polyamide
Insulating material group	I (CTI >= 600V)

Available colors

green	(similar to RAL 6032)
black	(similar to RAL 9005)
light grey	(similar to RAL 7035)
dark gray	(similar to RAL 7040)
orange	(similar to RAL 2003)
blue	(similar to RAL 5012)
red	(similar to RAL 3017)
another colors	(on demand)

Technical drawing



Derating curve

